



Airtight plastic access panels

Fully airtight and high level acoustic performance plastic access panels.



Use

- Provides access to services and connections behind dry lined walls, ducts, ceilings and cupboard units
- Complete solution to meet the highest levels of Building Regulation Part L and Building Regulation Part J and the gas safety industry's concealed boiler flue inspection requirements (non-fire rated applications)

Features and benefits

- Purpose made product saves time and money compared with traditional joiner-made or steel access doors
- Unique airtight seal design reduces the air permeability to 0.00/h.m at +50pa
- Flush fitting door panels that can be fully removed for maximum access
- Excellent aesthetic appearance and finish
- Textured finish allows painting if required
- Visible picture frame surround smartly conceals cut out edges and contributes to a faster installation
- Universal door handing
- Installed in minutes using basic hand tools and silicon/flexible sealant
- Clip fit door panels with catch clip closing mechanism
- Acoustic performance of 31dB (contact the Timloc Technical team for more information)

Quality

- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Helping to meet Building Regulation:
 - Document Part J - Concealed Flues in Voids (2010 edition)
 - Document Part E - Resistance To Sound
 - Part L1 and L2 - Conservation of Fuel and Power (2013 edition)

Material and colour choice

- Tough and UV stabilised injection moulded HIPS/ABS plastic
- White finish

Installation advice

- Cut hole to size, making sure that it is straight and level
- Apply silicon or other suitable grade building adhesive to the back of the frame
- Press the frame firmly into place, checking it is straight and level
- Do not operate until the adhesive has set completely
- Simply push the clip fit door panel into the frame

Care and maintenance

- Clean using a soft cloth with a mild detergent

How to order

- State which size of panel is required and confirm the hole cutting size

Bill of quantity

L20 Doors/Shutters/Hatches

Clause

630⁺ HATCHES

• Product Reference: **Timloc Access Panels**

• Type: **Timloc Airtight Access Panels**

• Product Code: **AP300AT (see other product codes/variation of sizes)**

• Frame fitting size: **305 x 305mm** (see other product codes/variation of sizes)

• Application: (example Wall, Ceiling, Cupboard or Voids)

• Frame type: **Picture**

• Colour: **Textured White ABS Plastic**

n55Plus

Product codes

Airtight plastic access panels

Frame fitting size	Clear opening size	Overall panel and frame dimension	Door type	Product code
115 x 165mm	100 x 150mm	135 x 185mm	Clip fit	AP110AT
155 x 235mm	140 x 220mm	195 x 275mm	Clip fit	AP150AT
205 x 205mm	190 x 190mm	245 x 245mm	Clip fit	AP200AT
305 x 305mm	290 x 290mm	345 x 345mm	Clip fit	AP300AT
470 x 470mm	455 x 455mm	510 x 510mm	Clip fit	AP450AT

